



SLM 2/2-way Pilot Operate Piston Solenoid Valve

●The Professional Solenoid Valves Manufactory

Main Technical Parameters

Serialized products, small in size, Large flow rate, widely use

Body material: Brass

Plunger tube material: brass stainless steel

Voltage: AC220V/6VA DC24V/6W (other voltage can special made)

Flow as the arrow, mounts in any position

Best position is solenoid vertical and upright direction

This series valve are offered NBR EPDM VITON for series and diaphragm to provide on-off control of various fluids.



Pipe Size	Orifice mm	CV	Working Pressure (bar)				Coil Type	Power		Coil Class	Model code LxWxH	Model Code Follows Voltage are AC220V 50/60HZ	Weight Kg	
			Min	Max		VA AC 220V		W DC 24V						
				Gas					Liquid					
				AC	DC				AC					DC
3/8"	12	2.4	0.5	16	12	16	12	D	6	6	F	62x43x84.2	SLM1DF02N1C12	0.44
	12	2.4	0.5	16	12	16	12	D	6	6	F	62x43x84.2	SLM1DF02E1C12	
	12	2.4	0.5	16	12	16	12	D	6	6	F	62x43x84.2	SLM1DF02V1C12	
1/2"	12	2.4	0.5	16	12	16	12	D	6	6	F	62x43x84.2	SLM1DF02N1D12	0.42
	12	2.4	0.5	16	12	16	12	D	6	6	F	62x43x84.2	SLM1DF02E1D12	
	12	2.4	0.5	16	12	16	12	D	6	6	F	62x43x84.2	SLM1DF02V1D12	
3/4"	20	6.0	0.5	16	12	16	12	D	6	6	F	80x60x93	SLM1DF02N1E20	0.8
	20	6.0	0.5	16	12	16	12	D	6	6	F	80x60x93	SLM1DF02E1E20	
	20	6.0	0.5	16	12	16	12	D	6	6	F	80x60x93	SLM1DF02V1E20	
1"	25	8.5	0.5	16	12	16	12	D	6	6	F	100x80x102	SLM1DF02N1G25	1.0
	25	8.5	0.5	16	12	16	12	D	6	6	F	100x80x102	SLM1DF02E1G25	
	25	8.5	0.5	16	12	16	12	D	6	6	F	100x80x102	SLM1DF02V1G25	

Configuration dimension chart

